



BATCH  
SYSTEMS



Parallel plate  
electrolyzer assembly

**KLOROGEN**<sup>®</sup>

SYSTEM RANGE

150 TO 3000 g/batch

(8 hrs)



MODELS	Equivalent Chlorine Output	1ppm	2ppm	3ppm	4ppm	5ppm	Plug Point Rating (Amps) with 220 VAC Single Phase 50Hz
	gm/batch (8hrs)	Volume of water that can be disinfected Kilo Litres Per Day (KLD) with 3 batches/day					Amps
RTCHLOR-BBT-15S	150	450	225	150	113	90	5.00
RTCHLOR-BBT-50S	550	1650	825	550	413	330	5.00
RTCHLOR-BBT-100S	1100	3300	1650	1100	825	660	15.00
							<b>Breaker Rating with 415 VAC 3 Phase 50Hz</b>
RTCHLOR-BBT-200S	2000	6000	3000	2000	500	1200	10.00
RTCHLOR-BBT-300S	3000	9000	4500	3000	750	1800	10.00



# batch system

for **stagewise production**  
**OF SODIUM HYPO-CHLORITE**

**RT CHLOR**® Batch systems are simple to install and operate. It can be made fully operational within few hours of receiving all the inputs at the installation. Each batch is considered for 8 hours of operation and it can be operated for 24 hours (in 3 batches) to augment the production. Locally available manpower can be trained in a day to operate the system.